

SUSTAINABILITY-DATASHEET

UZIN PE 260

Multipupose Primer

Indoor Air Quality (VOC)

EMICODE EC 1 PLUS - very low emission

Blue Angel according to RAL-UZ 113 - special environmental friendliness

Solvent-free



LEMICO

EC 1

LCA according to ISO 14040/44

Impact indicators:

Functional Unit (FU): 1 kg product; cradle-to-gate (according to EN 15804: Modules A1-A3)

[kg CO ₂ -Eq./kg]	0,58	Total use of non-renewable primary energy resources	[MJ/kg]	25,58
[kg R11-Eq./kg]	1,96E-07	Total use of renewable primary energy resources	[MJ/kg]	0,75
[kg SO ₂ -Eq./kg]	2,22E-03	Waste categories:		
[kg PO₄-Eq./kg]	4,98E-03	Hazardous waste disposed	[kg/kg]	4,51E-03
[kg Ethen-Eq./kg]	7,26E-04	Non-hazardous waste disposed	[kg/kg]	2,37E-01
[kg Sb-Eq./kg]	2,47E-07	Radioactive waste disposed	[kg/kg]	6,92E-05
[MJ/kg]	25,30	Use of net fresh water	[m³/kg]	0,28
	[kg R11-Eq./kg] [kg SO ₂ -Eq./kg] [kg PO ₄ -Eq./kg] [kg Ethen-Eq./kg] [kg Sb-Eq./kg]	[kg R11-Eq./kg] 1,96E-07 [kg SO2-Eq./kg] 2,22E-03 [kg PO4-Eq./kg] 4,98E-03 [kg Ethen-Eq./kg] 7,26E-04 [kg Sb-Eq./kg] 2,47E-07	[kg CO2-Eq./kg]0,58energy resources[kg R11-Eq./kg]1,96E-07Total use of renewable primary energy resources[kg SO2-Eq./kg]2,22E-03Waste categories:[kg PO4-Eq./kg]4,98E-03Hazardous waste disposed[kg Sb-Eq./kg]2,47E-07Radioactive waste disposed	[Kg CO2-Eq./Kg]0,58energy resources[MJ/kg][kg R11-Eq./kg]1,96E-07Total use of renewable primary energy resources[MJ/kg][kg SO2-Eq./kg]2,22E-03Waste categories:[MJ/kg][kg PO4-Eq./kg]4,98E-03Hazardous waste disposed[kg/kg][kg Sb-Eq./kg]2,47E-07Radioactive waste disposed[kg/kg]

Green Building / Certification of Buildings

DGNB – German Sustainable Building Council

Version 2015. Criteria: ENV 1.2 Risks for local environment (Risiken für die lokale Umwelt)

Product group according to matrix of criteria (Row 8): primer, sealants, levelling compounds and adhesives underneath wall an flooring coverings (for example tiles, textile floorcoverings, wood flooring, resilient flooring – except murals)

Quality level (QS)	Requirements	Compliant
QS 1	GISCODE D1, RU 0,5, RU1, RE1 or RS10	Yes
QS 2	EMICODE EC 1, EC1 Plus, EC1-R, EC1- R Plus or RAL-UZ 113	Yes
QS 3	EMICODE EC 1, EC1 Plus, EC1-R, EC1- R Plus or RAL-UZ 113	Yes
QS 4	EMICODE EC 1, EC1 Plus, EC1-R, EC1- R Plus or RAL-UZ 113	Yes

UZIN | A Brand of Uzin Utz AG

Dieselstrasse 3 | D-89079 Ulm | Telephone +49 (0)731 4097-0 | Telefax +49 (0)731 4097-110 | E-mail info@uzin.com | Internet www.uzin.com 1 of 2



Classification: Labelled with the EMICODE EC 1 Plus and the GISCODE D1 the product meets the highest DGNB quality level 4.

LEED – Leadership in Energy and Environmental Design

• Version 2014 (v4), updated 2017. Credit EQ: Low-Emitting Materials

Product group: Interior adhesives and sealants applied on site (including flooring adhesives).

Requirements:	Compliant
VOC content requirements for wet applied products: Compliance with VOC content according SCAQMD Rule 1168.	to Yes
General Emissions Evaluation: Compliance with emission limits according to AgBB scheme or Standard Method v1.1.	CDPH Yes

Classification: VOC content according to SCAQMD Rule 1168 is 13 g/L. Labelled with the EMICODE EC 1 Plus the product meets the emission limits according to the AgBB scheme. Thus, the product meets the requirements of LEED v4 for the low-emitting materials criteria.

• Version 2009, updated 2013. Credit IEQ 4.1: Low-Emitting Materials

Product group: Adhesives and Sealants

Requirement: Compliance with the VOC content according to SCAQMD Rule 1168.

Additional Test: VOC emission test according to CDPH Standard Method v1.1 is met.

Classification: VOC content according to SCAQMD Rule 1168 is 13 g/L. Thus, the product meets the requirements of LEED 2009 for the low-emitting materials criteria.

BREEAM - Building Research Establishment Environmental Assessment Methodology

Version 2016. Hea 02 Indoor air quality

Criteria Requirements on emission testing		Compliant			
Emission criteria (Table 17)	EN 13999 (Parts 1-4) or ISO 16000-9 or CEN/TS 16516 or CDPH	Yes			
Exemplary level emission criteria (Additional requirements Table 18)	Standard Method v1.1	Yes			

Classification: The product meets the emission limits according to BREEAM.

Certifications: Technical data sheet, Safety Data Sheet, license of EMICODE EC1 PLUS, certificate of the German Blue Angel and other product related information are available for download at www.uzin.com.

Remark:

This Sustainability Data Sheet is based on our findings and our experience at the time of the issue date. Additionally the data in the product data sheet and the safety data sheet have to be observed.

Contact: sustainability@uzin-utz.com

Issued 08/2017